

Omni16C Integral DC Power Supply

Model C1422 20 to 60Vdc Power Supply for Omni16C.

DATASHEET



Integral PSU Module

FEATURES

- DC Input Supply
- Field Isolation of 1500Vrms
- 20 to 60Vdc Input
- Modular retrofit option
- Powers both an Omni8C and an Omni16C (24-point system)

Tamananatuma Damana

The isolated power supply allows the Omni16C to be powered directly from a DC source thus avoiding the need for a separate external power supply for the annunciator.

The power supply module is fitted into the spare cavity within the Omni16C housing. It cannot be fitted to an Omni8C as space precludes this option, however the power supply module is capable of powering both an Omni16C and Omni8C together when used as a 24 Point annunciator. The Omni16C is fitted with the power supply module while the Omni8C is powered from the 24Vdc terminals on the Omni16C.

For dc applications such as substations the Omni16 may be powered from 20 to 60Vdc systems such as station back up supplies or it may be used to isolate the 24Vdc supply from the annunciator.

Omni16 is supplied standard as a 24V dc powered unit, the power supply option is specified at order time as an separate accessory and will be factory fitted.

Once the power supply module is fitted to the Omni16C a set of power terminals protrudes from the housing and the existing 24V power terminals are now become an Auxiliary 24V dc supply output to power an Omni8C for example.

SPECIFICATIONS

Power Supply Options		
Model No.	C1422	C1421
Voltage Option	20-60Vdc**	85-264Vac**
Input current at full load	<3A at 24Vdc <1.3A at 48Vdc	<1.5Arms at 115Vac <0.7A rms at 230Vac
Isolation PSU to inputs	1500Vrms	1500Vrms
Max dc Ripple	10% pk. to pk.	N/A
Maximum Load	24Vdc at 2.2A	
**To be ordered as an option: see accessories list. Fitted prior to shipment		

Temperature Range			
Operating Temperature Humidity	0 °C - 60 °C (+32 °F - 140 °F) Up to 90% RH, non condensing is recommended		
Storage Temperature Humidity	-10 °C - 70 °C (+14 °F - 158 °F) Less than 40% RH recommended		
Ordering Information			
Model Number D	escription		
-	Integral ac/dc PSU module. 85 - 264Vac or 100 - 240Vdc		
C1422 Integral	Integral dc PSU Module. 20 – 60Vdc		
* See Datasheet for more detail			

