



DATASHEET

- Designed for:
 - Process Control
 - Factory Automation
 - General Industrial Applications
- All Round Protection:
 - Short Circuit
 - Over Voltage
 - Over Current

DIN Rail Mounted

reliability even in harsh conditions.

Universal Input 90-264Vac Adjustable 24Vdc Output

Features

Overview

- Over Temperature
- Cooling by free air convection no fans

The POWERTERM "P" range of DIN rail mount 24Vdc power

supplies is specifically designed for industrial instrumentation applications. Use of carefully selected long-life components

and conservative design parameters ensure increased



-
- LED Indicator for DC Power On and DC Low
- 100% Full Load Burn-in Test
- 3 Year warranty

The POWERTERM P Series is part of the range POWERTERM industrial power supplies and battery chargers from Omniflex.

This third-generation family of power supplies uses the latest switch-mode supply technology to reduce cost, increase reliability and meet international safety and compatibility standards.

Models					
Model	Description	Input	Output	Dimensions (WxHxD)	Full Datasheet
C2203A	Powerterm P15-24	90-264Vac	24Vdc 0.65A	22.5 x 95 x108 mm	https://www.omniflex.com/products/C2203A
C2206A	Powerterm P70-24	90-264Vac	24Vdc 3A	33 x 130 x125 mm	https://www.omniflex.com/products/C2206A
C2207A	Powerterm P120-24	90-264Vac	24Vdc 5A	40 x 130 x125 mm	https://www.omniflex.com/products/C2207A
C2209A	Powerterm P240-24	90-264Vac	24Vdc 10A	60 x 130 x125 mm	https://www.omniflex.com/products/C2209A



